



7437 Village Square Lane, Suite #215, Castle Pines, CO 80108

303-705-0227 Fax 303-688-9414

City of Castle Pines Residential Roofing Requirements

- 1. A permit shall be required on any re-roofing project or any roof repair that requires more than 100 square feet of the roof to be replaced
- 2. Asphalt shingles shall meet the ASTM D-3161, Class A, D, or F Testing installation requirements or ASTM D 7158, Class G or H
- 3. Drip edge flashing is required on all eaves and rake edges.
- 4. Fasteners; Roofing nails that extend through the underside of the roof sheathing, or a minimum of 3/4" into the roof decking
- Inspector shall verify the ASTM testing standards imprinted on the shingle packaging
- 6. Ice Barrier is not required
- 7. Valley linings
 - a. Open Valleys—shall be metal at least 24" wide of any corrosion resistant metal
 - b. Open Valleys—2 plys of mineral surfaced roll roofing. Bottom layer shall be 18" wide, top layer shall be 36" wide
 - c. Closed Valleys—lining can be 1 layer of smooth roll roofing and at least 36" wide. A self-adhering polymer modified bitumen underlayment shall be permitted in lieu of the lining material
- 8. A ladder must be on-site; tied off to the roof for the inspection
- 9. Mid-roof inspections are only required on flat and tile roofs

The City of Castle Pines Design Criteria;

- 105 MPH, 3-second gust
- Wind Exposure category "B"